ITEM NO	ITEM	UNIT	ORIG	FINAL
402.15	CRUSHED STONE SHOULDERS (MOD)	TON	30	
406.25	BITUMINOUS CONCRETE PAVEMENT	TON	40	

SIGNAL CONTROL BASE WILL BE LOCATED A MINIMUM DISTANCE OF 30 FEET FROM THE EDGE OF ROADWAY PAVEMENT UNLESS EXISTING CONDITIONS WARRANT REDUCING THIS DISTANCE, IN WHICH CASE THE LOCATION WILL BE RESOLVED BY THE PARTIES CONCERNED.

Proj. POT. 0+00.0

Proj. POT. 4+50.00+

Barn

Cemetery

Warehouse

Shed

Cattle Pass

APPROX. LOCATION OF RR SIGNAL LIGHTS

APPROX LOC. OF RR SIGNAL LIGHTS

Construction Area

Proj. POT. 15+33.0 +
M.L. POT. 19+33.0
Δ 50° 27' Rt.

Proj. PI. 14+20.44
Δ 14° 48' Lt.

B.M. #1
USGS B.M. P. 12 (1922)
Disc in Conc. Step
Elev. 440.23

APPROX LOCATION OF RR. SIGNAL LIGHTS

TO RICHFORD RUBLEE ROAD

POT. 24+19.86

SURVEYED BY: Survey 1 DATE: Aug. 75
DRAWN BY: Stevens DATE: 8/75
TRACED BY: DATE:

BERKSHIRE

PROJ. RRS NO. 0005(4)

SHEET 2 OF

2